

2024-3-27 | Data subject to change without notice

Wall Light | Ø160mm | 6W | IP65 |  
2700-3000K

Article number: 136-255



This IK08 wall mounted luminaire with UV resistant and corrosion resistant material is suitable for various (industrial) applications. For example, lighting of tunnels, parking garages or walkways. In addition, the fixture is also adjustable in two light colors (2700K-3000K).

## Features

- ADC12 aluminum housing with good heat dissipation
- PC 94-V0 anti-UV plastic housing
- 94-V2 corrosion resistant diffuser
- IP65 waterproof
- CCT-2 switch: adjustable in 2700K and 3000K by means of a dip-switch in the fixture
- Available in two sizes

## Specifications

Type	Wall light	CRI value	>80	Diameter	Ø 160 mm
Input voltage	230V	Driver	Incl. internal driver	Connection type	Terminal block
Power	6 Watt	Power factor	>0.90	Housing material	PC
Luminous flux	400 Lm	Beam angle	120°	Housing color	Black
Color temperature	2-CCT	Adjustable	Yes	Certification mark	CE, RoHS
Light color	Extra warm white - warm white (2700K- 3000K)	IP rate	IP65	Warranty	5 years
Dimmable	No	Mounting	Surface		
Lifetime	L70B50 (50.000 hours)	Sensor	No		

