

LED PANEL

RESI FLOODLIGHT-100W-3000K-IP65-GRIS

BL101006503B

OUTDOOR > Outdoor Flood Light

Residential projector that meets the regulations on light pollution. Discreet and aesthetic, it fits well on the facade and is very effective in indirect lighting

**Application domain**

- Outdoor residential
- Garden
- Outdoor lighting



100 W

8600
lmIRC
>80

IP65

3000K

F

Electric data

Total power (W)	100
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	3000K
Light source type	-
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	8600lm (3000K)
ULOR	-

Technical data

Dimensions (mm)	31 x 276 x 205
Weight (kg)	1.56
Recessed depth under BA13 (mm)	-
Cable length	100 cm
Product color	Grey
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	Verre trempé
Driver included	Yes

Liefe time

L70 à 25°	35 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">• TR08006501 - CONNECTOR IP65