

LED PANEL

EDGE-36W-4000K- LOT DE 2 PIECES

PL04362001

INDOOR > Office Recessed Fixture

LED edge panel, ideal for the tertiary sector, robust and economical, it is equipped with a safety rope and a quick connection terminal block. One package=1 reference: contains 2 pieces



Application domain

- Meeting room
- School
- Office
- Medical areas
- Circulations areas
- Cloakrooms
- Shop



36 W

3600
lm

UGR
<19*

IRC
>80

IP20

4000K



Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
UGR	<19*
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3600lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 9
Weight (kg)	2.56
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	120°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL08000013 - TF066-Protrusion frame 600x600• BL08000002 - TF018 Mechanically welded projection frame• BL08000006 - SUSPENSION KIT 600x600 tile• BL08000009 - INTEGRATION FRAME 600x600