

TF128-DOWNLIGHT 3CCT SEMI ENCASTRE/SAILLIE 18W SENSOR-IP44

BL02182004

INDOOR > Downlight (100 to 240 mm)

INDOOR > Surface mounted and suspended fixtures

Downlight with 3 temperature colors. Can be installed both surface-mounted and recessed using the included accessories. Recessing adjustable from 55 to 175 mm! With IR (infra-red) presence detector and safety cable.



Application domain

- Residential indoor
- Office
- Home Office
- Circulations areas



18 W

1650
lm

IRC
>80

IP44

3 CCT

3000K / 4000K
6500K

F

Electric data

Total power (W)	18
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 6500K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1650lm (4000K)
ULOR	-

Technical data

Diameter (mm)	217
Height (mm)	15
Recessed diameter (mm)	Min. : 55 Max. : 175
Weight (kg)	0.5
Recessed depth under BA13 (mm)	20
Cable length	30 cm
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP44
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Sensor	Infra rouge
Driver included	Yes

Liefe time

L70 à 25°	30 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	Yes
Connection type	Fil à connecter

Atmosphere



Other

