


OFFICE LINE

TF135-OFFICELINE 120-NR-30W-CCT-UGR19

BL06272001

INDOOR > Surface mounted and suspended fixtures

Ceiling LED suspension, Suspended or surface-mounted strip.
UGR19 with optional 30% / 70% indirect lighting. Chrome reflector
Low luminance. Possible online accessory



Application domain

- Meeting room
- Office



30 W

3500
lm

UGR
<19

IRC
>80

IP20

3 CCT

3000K / 4000K
5700K



Electric data

Total power (W)	30
Rated voltage (V)	230V
Distorsion harmonique	<10%
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	No



FILE UPDATED ON 09/03/2023

Power supply data

Max. lamp per B10A circuit breaker	8
Max. lamp per B16A circuit breaker	12
Max. lamp per C16A circuit breaker	16

Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	3500lm (4000K)
ULOR	-



FILE UPDATED ON 09/03/2023



Technical data

Dimensions (mm)	1130 x 50 x 72
Weight (kg)	1.78
Recessed depth under BA13 (mm)	-
Cable length	150 cm
Product color	Black
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	-
Driver included	No

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	80°
Tiltable	No
Connection type	Fil à connecter



FILE UPDATED ON 09/03/2023



Atmosphere



Other



Other



FILE UPDATED ON 09/03/2023