


# TF092-FOG-20W-IP66-WHITE-3000K-850

BL12206502

**INDOOR** > Indoor Bulkhead  
**OUTDOOR** > Outdoor Wall Light  
**OUTDOOR** > Outdoor Bulkhead

Indoor or outdoor use, IP66, available with detector. Ideal for communities, garages and stairwells



## Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



## Electric data

Total power (W)	20
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No



FILE UPDATED ON 21/11/2022

## Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2030lm (3000K)
ULOR	-

## Technical data

Diameter (mm)	300
Height (mm)	93.5
Recessed diameter (mm)	-
Weight (kg)	0.9
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20... +50°
Body material	PC
Diffuser material	PC
Driver included	Yes



FILE UPDATED ON 21/11/2022



## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Fast connect

## Atmosphere



## Other



FILE UPDATED ON 21/11/2022



FILE UPDATED ON 21/11/2022