

LED PANEL

PANEL SAILLIE 600X600-3CCT-3P-IP65 FACADE

BL04365401

INDOOR > Office Recessed Fixture

INDOOR > Surface mounted and suspended fixtures

Projecting led panel. To be installed directly on the ceiling without using an additional frame. 3 temperature colors and 3 powers! 9 products in 1!



Application domain

- Meeting room
- Office
- Medical areas
- Circulations areas
- Cloakrooms
- Outdoor Circulations



30 W

3600
lm

UGR
<19*

IRC
>80

IP65
facade

3 CCT

3000K / 4000K
6000K



Electric data

Total power (W)	30 / 36 / 42
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 6000K
UGR	<19*
Light source type	-
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3600lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 50
Weight (kg)	2.18
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP65 facade
Use temperature range	-
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non concerné

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No