

SLIM

# CAMUS UGR19 25W-IP44-4000K-WHITE

TR02254405B

**INDOOR** > Downlight (100 to 240 mm)

Thin downlight with prismatic diffuser.

## Application domain

- Meeting room
- Office
- Circulations areas



25 W

2135  
lm

UGR  
<19

IRC  
>80

IP44  
facade

4000K



## Electric data

Total power (W)	25
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III
Dimmable	No



FILE UPDATED ON 17/04/2023

## Photometric data

Color temperatures	4000K
UGR	<19
Light source type	-
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2135lm (4000K)
ULOR	-

## Technical data

Diameter (mm)	240
Height (mm)	13
Recessed diameter (mm)	Min. : 220   Max. : 235
Weight (kg)	0.75
Recessed depth under BA13 (mm)	35
Cable length	-
Product color	White
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP44 facade
Use temperature range	-25... +40°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable



FILE UPDATED ON 17/04/2023



## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	100°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none"><li>PL09002001B - DALI PUSH POWER SUPPLY Camus</li></ul>

## Other

---



FILE UPDATED ON 17/04/2023

