

CYLINDER

# CYLINDER 1500-DIAM70-50W-IP65-4000K- OPAL

TR11506506

**INDOOR** > Surface mounted and suspended fixtures

**INDOOR** > Wall light

**INDOOR** > Triproof

Waterproof LED tubular LED pendant luminaire in polycarbonate and aluminium. Fixing accessories in 316L stainless steel.



## Application domain

- Industrial facilities
- Parkings lots and underground passages
- Garages



## Electric data

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	No

## Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	5000lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	1510 x 75 x 75
Weight (kg)	1.88
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	-
IK Code	IK10
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	PC - STAINLESS STEEL 316L
Diffuser material	PC
Driver included	Yes

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	Yes (360°)
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none"><li>• TR11000001 - CYLINDER SUSPENSION KIT</li><li>• TR11000002 - CYLINDER CABLE 3M TRANSL</li><li>• TR11000005 - CYLINDER BOX CONNECTION</li></ul>