

LED DOWNLIGHT

VISUAL-25W-IP54-3CCT

BL02255411

INDOOR > Downlight (100 to 240 mm)

Low-glare LED downlight, 3CCT and IP54, ideal for the service sector: hallway, meeting room. Option in Dali possible Visual range



Application domain

- Meeting room
- School
- Office
- Medical areas
- Circulations areas
- Cloakrooms
- Washrooms
- Entrance Halls
- Shop



25 W

2700
lm

UGR
<19

IRC
>80

IP54
facade

3 CCT

3000K / 4000K
5700K



FILE UPDATED ON 28/03/2023

Electric data

Total power (W)	25
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III (II with power supply)
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	2700lm (4000K)
ULOR	-



FILE UPDATED ON 28/03/2023



Technical data

Diameter (mm)	228
Height (mm)	107
Recessed diameter (mm)	Min. : 200 Max. : 220
Weight (kg)	1.08
Recessed depth under BA13 (mm)	110
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP54 facade
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L80 à 25°	50 000 h
-----------	----------



FILE UPDATED ON 28/03/2023




Supplementary data

Warranty period	5 years
Light beam spread	63°
Tiltable	No
Connection type	Connector on the product
Linked products	<ul style="list-style-type: none">• BL02185410 - VISUAL DOWNLIGHT-18W-3CCT-IP54• BL02505412 - VISUAL DOWNLIGHT-50W-3CCT-IP54• BL02185415 - VISUAL DOWNLIGHT-18W-3CCT-IP54• BL09302011 - POWER SUPPLY DALI-PUSHDIM-25W

Other



Other



FILE UPDATED ON 28/03/2023