

THICK HEADED

BORNE 24W-IP65-3000K

BL17246501

OUTDOOR > Bollard

LED bollard for PMR standard, in aluminium, anthracite grey, 24W, with 360 degree lighting. IK10. Anti-glare system with very good uniformity. 3000K and ULR ≤ 0 which meets light pollution regulations.



Application domain

- Outdoor residential
- Garden
- Outdoor illumination
- Outdoor Circulations
- Outdoor lighting



Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1600lm (3000K)
ULOR	-

Technical data

Diameter (mm)	160
Height (mm)	995
Recessed diameter (mm)	-
Weight (kg)	5.34
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Dark gray
IK Code	IK10
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +40°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	360°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">• BL17240001 - HALF ACCESSORY TERMINAL

