

RECESSED

WINDOW 40W-3CCT-BL

BL02402010

INDOOR > Downlight (100 to 240 mm)

Adjustable high-power recessed light, ideal for shop windows and for showcasing products on shelves. Adjustable color temperature on the product to adapt perfectly to the desired atmosphere.



Application domain

- Entrance Halls
- Shop



40 W

4100
lmIRC
>80

IP20

3 CCT

3000K / 4000K
5700K

D

Electric data

Total power (W)	40
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 5700K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	4100lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	156 x 246 x 144
Recessed diameter (mm)	Min. : 130 Max. : 225
Weight (kg)	2.26
Recessed depth under BA13 (mm)	150
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	Verre trempé
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	90°
Tiltable	Yes (90°)

Atmosphere



Other



Other

