

LED DOWNLIGHT

THOR 2- 25W-4000K-60°-BL

BL02252010

INDOOR > Downlight (100 to 240 mm)

Snail type accent adjustable recessed downlight for display in shops. Rotatable 360° around the vertical axis



Application domain

- Entrance Halls
- Shop



25 W

2200
lm

UGR
<19

IRC
>80

IP20

4000K



Electric data

Total power (W)	25
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
UGR	<19
Light source type	COB
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	2200lm (4000K)
ULOR	-

Technical data

Diameter (mm)	180
Height (mm)	100
Recessed diameter (mm)	Min. : 160 Max. : 170
Weight (kg)	1.18
Recessed depth under BA13 (mm)	120
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	-
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	60°
Tiltable	Yes (45°)
Connection type	Connector on the product

