

LED DOWNLIGHT

VISUAL-50W-IP54-3CCT-3PUI

BL02505412

INDOOR > Downlight (100 to 240 mm)

Low glare LED downlight, 3CCT and IP54, ideal for high ceilings: showrooms, stores, concessions... Visual range



Application domain

- Meeting room
- School
- Office
- Medical areas
- Circulations areas
- Cloakrooms
- Washrooms
- Entrance Halls
- Shop



FILE UPDATED ON 08/03/2023

Electric data

| | |
|-----------------------|----------------------------|
| Total power (W) | 50 |
| Rated voltage (V) | 230V |
| Distorsion harmonique | - |
| Power factor | >0.9 |
| Network frequencies | 50Hz |
| Electric class | III (II with power supply) |
| Dimmable | No |

Photometric data

| | |
|----------------------------|-----------------------|
| Color temperatures | 3000K / 4000K / 5700K |
| UGR | <19 |
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>3 |
| IRC | >80 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 4900lm (4000K) |
| ULOR | - |



FILE UPDATED ON 08/03/2023



Technical data

| | |
|--------------------------------|-------------------------|
| Diameter (mm) | 280 |
| Height (mm) | 123 |
| Recessed diameter (mm) | Min. : 230 Max. : 260 |
| Weight (kg) | 1.62 |
| Recessed depth under BA13 (mm) | 130 |
| Cable length | - |
| Product color | White |
| IK Code | IK06 |
| Incandescent wire test | 650°C |
| IP Code | IP54 facade |
| Use temperature range | -25... +45° |
| Body material | Aluminium |
| Diffuser material | PC |
| Driver included | No |
| Recoverable | Non recouvrable |

Liefe time

| | |
|-----------|----------|
| L80 à 25° | 50 000 h |
|-----------|----------|


Supplementary data

| | |
|-------------------|--------------------------|
| Warranty period | 5 years |
| Light beam spread | 63° |
| Tiltable | No |
| Connection type | Connector on the product |



FILE UPDATED ON 08/03/2023





FILE UPDATED ON 08/03/2023