

# TF127-DOWNLIGHT 3CCT SEMI ENCASTRE/SAILLIE 18W-IP44 FACADE

BL02182003

**INDOOR** > Downlight (100 to 240 mm)

**INDOOR** > Surface mounted and suspended fixtures

Downlight with 3 temperature colors. Can be installed both surface-mounted and recessed using the included accessories. Safety clip included



## Application domain

- Residential indoor
- Office
- Home Office
- Circulations areas



18 W

1650  
lm

IRC  
>80

IP44

3 CCT

3000K / 4000K  
6500K

F



FILE UPDATED ON 08/11/2022

## Electric data

Total power (W)	18
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	3000K / 4000K / 6500K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1650lm (4000K)
ULOR	-



FILE UPDATED ON 08/11/2022



## Technical data

Diameter (mm)	217
Height (mm)	15
Recessed diameter (mm)	Min. : 55   Max. : 175
Weight (kg)	0.43
Recessed depth under BA13 (mm)	20
Cable length	30 cm
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP44
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Driver included	Yes

## Liefe time

L70 à 25°	30 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	Yes
Connection type	Fil à connecter



FILE UPDATED ON 08/11/2022



## Atmosphere



## Other



FILE UPDATED ON 08/11/2022