

LINE

LINE 9W-3000K-36°-DIM-NR

BL02092002

INDOOR > Downlights (until 95 mm)

INDOOR > Downlight (100 to 240 mm)

9W architectural downlight. Contemporary atmosphere for this low luminance downlight which perfectly complements the other products in the Line UGR<19 range



Application domain

- Residential indoor
- Kitchen
- Bedroom
- Home Office
- House Corridor



Electric data

Total power (W)	9
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Photometric data

Color temperatures	3000K
UGR	<19
Light source type	-
Including the light source	Yes
SDCM	SDCM>4
IRC	>90
Safety group (EN62778)	RG1
Luminous flux (lm)	500lm (3000K)
ULOR	-

Technical data

Dimensions (mm)	105 x 45 x 51
Recessed diameter (mm)	Min. : 37 Max. : 97
Weight (kg)	0.24
Recessed depth under BA13 (mm)	60
Cable length	-
Product color	Black
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP40
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	36°
Tiltable	No
Connection type	Connector on the product

