

PANEL EDGE 36W

TF011-PANEL ECO UGR19 600x600-36W-3480lm-cadre WHITE-4000K

BL04452004

INDOOR > Office Recessed Fixture

Very low height UGR<19* LED panel for meeting rooms, open spaces and offices.



Application domain

- Meeting room
- Office



Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	III (II with power supply)
Dimmable	No



FILE UPDATED ON 25/04/2023

Photometric data

Color temperatures	4000K
UGR	<19*
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>6
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3480lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 8
Weight (kg)	2.32
Recessed depth under BA13 (mm)	-
Cable length	20 cm
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP20 - IP40 front
Use temperature range	-20... +50°
Body material	Aluminium - PC
Diffuser material	PC
Driver included	Yes
Recoverable	Insulation material except driver



FILE UPDATED ON 25/04/2023



Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none">• BL08000013 - TF066-Protrusion frame 600x600• BL08000002 - TF018 Mechanically welded projection frame• BL08000006 - SUSPENSION KIT 600x600 tile• PL09302003 - DALI PUSH DIM POWER SUPPLY• BL08000009 - INTEGRATION FRAME 600x600



FILE UPDATED ON 25/04/2023

