

SPOT

TILT II-RECESSED-10W-IP20-3CCT-BLACK-DIM BL05102011

INDOOR > Surface mounted and suspended fixtures

Aesthetic product, allows to direct the flow at 360°! 3CCT and dimmable, Available November 2022.



Application domain

- Residential indoor
- Kitchen
- Bedroom
- Home Office
- House Corridor
- Shop



Electric data

Total power (W)	10
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Photometric data

Color temperatures	3000K / 4000K / 6000K
Light source type	COB
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	960lm (4000K)
ULOR	-

Technical data

Diameter (mm)	100
Height (mm)	100
Recessed diameter (mm)	Min. : 85 Max. : 90
Weight (kg)	0.5
Recessed depth under BA13 (mm)	25
Cable length	-
Product color	Black
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	36°
Tiltable	Yes (360°)
Connection type	Fast connect

