

RECESSED SPOTLIGHT

# STORM ASYMETRIC 8W-IP20-40°-3000K- ROND-WHITE

TR01082008

**INDOOR** > Downlights (until 95 mm)

Asymmetrical led spotlight. This spot will allow you to illuminate and highlight vertical surfaces.



## Application domain

- Residential indoor
- Bedroom
- Home Office
- Entrance Halls
- Shop



8 W

650 lm

IRC  
>80

IP20

3000K

D

## Electric data

Total power (W)	8
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

## Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	650lm (3000K)
ULOR	-

## Technical data

Diameter (mm)	90
Height (mm)	95.5
Recessed diameter (mm)	Min. : 77   Max. : 80
Weight (kg)	0.3
Recessed depth under BA13 (mm)	85
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	38°
Tiltable	No

## Atmosphere

---



## Other

---

