

CYLINDER

# CYLINDER 600 DIAM70-20W-IP65-4000K- TRANSPARENT

TR11206502

**INDOOR** > Surface mounted and suspended fixtures

**OUTDOOR** > Outdoor Wall Light

**INDOOR** > Wall light

**INDOOR** > Triproof

**OUTDOOR** > Ceiling Lights

Waterproof tubular luminaire in polycarbonate and stainless steel.  
Suspended or projecting, it is both aesthetic and technical.



## Application domain

- Production areas, assembly plant
- Outdoor illumination
- Medical areas
- Circulations areas
- Outdoor Circulations
- Locaux techniques
- Outdoor lighting



20 W

1800  
lm

IRC  
>80

IP65

4000K

D

## Electric data

Total power (W)	20
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	No

## Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1800lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	75 x 618 x 75
Weight (kg)	1.12
Recessed depth under BA13 (mm)	-
Cable length	100 cm
Product color	-
IK Code	IK10
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-20... +45°
Body material	PC - STAINLESS STEEL 316L
Diffuser material	PC
Driver included	Yes

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	Yes (360°)
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none"><li>• TR11000001 - CYLINDER SUSPENSION KIT</li><li>• TR11000002 - CYLINDER CABLE 3M TRANSL</li><li>• TR11000005 - CYLINDER BOX CONNECTION</li></ul>

## Atmosphere

---



## Other

---

