

## LED STRIP

# LEDSTRIP PRO+ 3M-19,2W/M-IP20-3000K

BL21202018

## LED STRIP > LED Strip

LED strip with a flux greater than 3400lm/m. Ideal for direct or indirect functional lighting. Sectionable every 5cm. Power cables at both ends. 3M adhesive on the back of the tape for easy installation.



### Application domain

- Residential indoor
- Meeting room
- Office
- Kitchen
- Bedroom
- Home Office
- House Corridor
- Backlight
- Home Cellar, House Technical Room
- Circulations areas
- Stairs
- Entrance Halls
- Shop



FILE UPDATED ON 06/10/2022

## Electric data

Total power (W)	19.2
Rated voltage (V)	24Vdc
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	0Hz
Electric class	III
Dimmable	Triac , Dali , 1-10V

## Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>3
IRC	>90
Safety group (EN62778)	RG1
Luminous flux (lm)	3456lm (3000K)
ULOR	-



FILE UPDATED ON 06/10/2022



## Technical data

Weight (kg)	0.04
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK02
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	-
Diffuser material	-
Driver included	No

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data


Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	Fil à connecter



FILE UPDATED ON 06/10/2022



# Plan



FILE UPDATED ON 06/10/2022

