

LED SPOTLIGHT

STORM LOW GLARE 8W-IP20-40°-3000K- ROND-WHITE

TR01082003

INDOOR > Downlights (until 95 mm)

Aluminum low luminance spotlight. Very nice rendering without dazzling.



Application domain

- Residential indoor
- Kitchen
- Bathroom
- Bedroom
- Home Office
- House Corridor



8 W

650 lm

UGR
<19IRC
>80

IP20

3000K



Electric data

Total power (W)	8
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Photometric data

Color temperatures	3000K
UGR	<19
Light source type	COB
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	650lm (3000K)
ULOR	-

Technical data

Diameter (mm)	90
Height (mm)	86
Recessed diameter (mm)	Min. : 77 Max. : 85
Weight (kg)	0.28
Recessed depth under BA13 (mm)	86
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	40°
Tiltable	No

