



in partnership with

# **DRIVER RF-50W-1CH-24V**

BL09502410

## LED STRIP > LED Strip DRIVERS AND ACCESSORIES > Alimentation et Accessoires

24V 50W power supply for color temperature. 1 channel

	Bankin union .	
•	C. CLOUDERVEYS NG	

IP20
------

#### **Electric data**

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	push dim , yes with RF remote controller



FILE UPDATED ON 24/01/2023

TOPLED NORDIC BE-LED. ALL RIGHTS RESERVED.

DRIVER RF-50W-1CH-24V - 1/3

#### **Photometric data**

Color temperatures	
Light source type	-
SDCM	
IRC	
Safety group (EN62778)	
Luminous flux (lm)	-
ULOR	

#### **Technical data**

Dimensions (mm)	210 x 50 x 32
Weight (kg)	0.26
Recessed depth under BA13 (mm)	-
Cable length	0
Product color	White
IK Code	IK04
Incandescent wire test	-
IP Code	IP20
Use temperature range	-20 +45°
Body material	PC
Diffuser material	-
Driver included	No
Recoverable	Non recouvrable

#### Liefe time



FILE UPDATED ON 24/01/2023

TOPLED NORDIC BE-LED. ALL RIGHTS RESERVED.


DRIVER RF-50W-1CH-24V - 2/3

### Supplementary data

Warranty period	5 years	
Light beam spread		
Tiltable	No	
Connection type	Fast connect	

Plan

Other





FILE UPDATED ON 24/01/2023