

TECH LED PANEL

# PANEL TECH IP65 FACADE-600X600-3CCT-3 PUI

BL04365402

**INDOOR** > Office Recessed Fixture

LED panel with 3 temperature colors and IP65 front. Driver adjustable in power: 30W (3600lm), 36W (4150lm) and 40W (4600lm) for 4000K Ideal for clean rooms, playground, locker room.



## Application domain

- Production areas, assembly plant
- Medical areas
- Washrooms
- Outdoor Circulations



## Electric data

Total power (W)	40
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	3000K / 4000K / 6000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	4600lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	595 x 595 x 26
Weight (kg)	1.7
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP20 - IP65 facade
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Insulation material except driver

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Connecteur rapide avec repiquage
Linked products	<ul style="list-style-type: none"><li>• BL08000013 - TF066-Protrusion frame 600x600</li><li>• BL08000002 - TF018 Mechanically welded projection frame</li><li>• BL08000009 - INTEGRATION FRAME 600x600</li></ul>

