

CYLINDER

CYLINDER 600 DIAM100-30W-IP67-4000K- TRANSPARENT

TR11306701

INDOOR > Surface mounted and suspended fixtures

OUTDOOR > Outdoor Wall Light

INDOOR > Wall light

INDOOR > Triproof

OUTDOOR > Ceiling Lights

Waterproof tubular luminaire in polycarbonate and stainless steel. Suspended or projecting, it is both aesthetic and technical. Tridonic brand power supply



Application domain

- Production areas, assembly plant
- Outdoor illumination
- Medical areas
- Circulations areas
- Outdoor Circulations
- Locaux techniques
- Outdoor lighting



30 W

2600
lm

IRC
>80

IP65

4000K

D

Electric data

Total power (W)	30
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2600lm (4000K)
ULOR	-

Technical data

Diameter (mm)	100
Height (mm)	105
Recessed diameter (mm)	-
Weight (kg)	1.6
Recessed depth under BA13 (mm)	-
Cable length	50 cm
Product color	-
IK Code	IK10
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-20... +45°
Body material	PC - STAINLESS STEEL 316L
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	Yes (360°)
Connection type	Fil à connecter

Atmosphere



Other

