

STORM RESI

# STORM CCT BBC-7W-4 COUL TEMP-RECOUV-DIM 2 COLL BL ALU

TR01076501B

**INDOOR** > Downlights (until 95 mm)

8 products in 1: Spot CCT 2700K-3000K-4000K-6000K delivered with 2 bezels, a single product for all home applications! With connection terminal block with quick tapping. Coverable insulation roll.



## Application domain

- Residential indoor
- Kitchen
- Bathroom
- Bedroom
- Home Office
- House Corridor



FILE UPDATED ON 16/02/2023

## Electric data

Total power (W)	6 / 6.5
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	Triac

## Photometric data

Color temperatures	2700K / 3000K / 4000K / 6000K
UGR	<19
Light source type	COB
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	500lm (3000K)
ULOR	-



FILE UPDATED ON 16/02/2023



## Technical data

Diameter (mm)	85
Height (mm)	62
Recessed diameter (mm)	Min. : 70   Max. : 76
Weight (kg)	0.26
Recessed depth under BA13 (mm)	50
Cable length	0
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65 facade
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Tout isolant

## Liefe time

L70 à 25°	50 000 h
-----------	----------



FILE UPDATED ON 16/02/2023



## Supplementary data

Warranty period	5 years
Light beam spread	60°
Tiltable	No
Connection type	Bornier avec repiquage
Linked products	<ul style="list-style-type: none"><li>• TR01076502 - SQUARE FLANGE ALU STORM</li><li>• TR01076503 - STORM ROUND BLACK BLANKET</li><li>• TR01076504 - STORM BLACK SQUARE BLANKET</li></ul>

## Accessories



## Atmosphere



FILE UPDATED ON 16/02/2023





FILE UPDATED ON 16/02/2023