

# TF100-FOG ASYM SENSOR-25W-IP66-WHITE-3000K-850°

BL12256504

**INDOOR** > Indoor Bulkhead**OUTDOOR** > Outdoor Wall Light**OUTDOOR** > Outdoor Bulkhead

Asymmetrical porthole with HF detector ideal for stairways, passageways and building surroundings.



## Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



24 W

2400  
lmUGR  
<25IRC  
>80

IP66

3000K



## Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	3000K
UGR	<25
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2400lm (3000K)
ULOR	-

## Technical data

Diameter (mm)	310
Height (mm)	115
Recessed diameter (mm)	-
Weight (kg)	1.22
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Sensor	Haute fréquence
Driver included	Yes

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	110° X 90°
Tiltable	No
Connection type	Fast connect

