

PROJECTOR

TF082-TECH PROJECTOR 150W-IP65-4000K- 120°

BL101506501

OUTDOOR > Outdoor Flood Light

High power led projector, tempered glass and aluminum body.
Sosen brand power supply.



Application domain

- Outdoor illumination
- Outdoor Parking
- Outdoor lighting



150 W

18200
lmIRC
>80

IP65

4000K



Electric data

| | |
|-----------------------|------|
| Total power (W) | 150 |
| Rated voltage (V) | 230V |
| Distorsion harmonique | - |
| Power factor | >0.9 |
| Network frequencies | 50Hz |
| Electric class | I |
| Dimmable | No |

Photometric data

| | |
|----------------------------|-----------------|
| Color temperatures | 4000K |
| Light source type | SMD |
| Including the light source | Yes |
| SDCM | SDCM>5 |
| IRC | >80 |
| Safety group (EN62778) | RG1 |
| Luminous flux (lm) | 18200lm (4000K) |
| ULOR | - |

Technical data

| | |
|--------------------------------|----------------|
| Dimensions (mm) | 63 x 494 x 309 |
| Weight (kg) | 6.68 |
| Recessed depth under BA13 (mm) | - |
| Cable length | 50 cm |
| Product color | Black |
| IK Code | IK08 |
| Incandescent wire test | 650°C |
| IP Code | IP65 |
| Use temperature range | -25... +45° |
| Body material | Aluminium |
| Diffuser material | Verre trempé |
| Driver included | Yes |

Liefe time

| | |
|-----------|----------|
| L80 à 25° | 50 000 h |
|-----------|----------|

Supplementary data

| | |
|-------------------|---|
| Warranty period | 5 years |
| Light beam spread | 120° |
| Tiltable | No |
| Connection type | Fil à connecter |
| Linked products | <ul style="list-style-type: none">TR08006501 - CONNECTOR IP65 |

