

## DOWNLIGHT

# DOWNLIGHT LED 13W-3CCT-IP54-90°-BL

BL02135401

**INDOOR** > Downlights (until 95 mm)

**INDOOR** > Downlight (100 to 240 mm)

**OUTDOOR** > Downlights (until 95 mm)

1000lm led downlight with opal diffuser. 90° opening ideal for the tertiary sector or collective residential for heights greater than 2.50m



### Application domain

- Home Office
- House Corridor
- Medical areas
- Circulations areas
- Cloakrooms
- Washrooms
- Entrance Halls



13 W

1300  
lm

IRC  
>80

IP54

3 CCT

3000K / 4000K  
5700K

E



FILE UPDATED ON 30/03/2023

## Electric data

Total power (W)	13
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

## Photometric data

Color temperatures	3000K / 4000K / 5700K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1300lm (4000K)
ULOR	-



FILE UPDATED ON 30/03/2023



## Technical data

Diameter (mm)	145
Height (mm)	97
Recessed diameter (mm)	Min. : 125   Max. : 130
Weight (kg)	0.22
Recessed depth under BA13 (mm)	100
Cable length	-
Product color	White
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP54
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Driver included	Yes
Recoverable	Isolant rouleau

## Liefe time

L70 à 25°	35 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	90°
Tiltable	No



FILE UPDATED ON 30/03/2023





FILE UPDATED ON 30/03/2023