

LED PANEL

# PANEL TECH-IP65 TOTAL-600X600-40W-4000K

BL04366502

**INDOOR** > Office Recessed Fixture

Complete IP65 &quot;backlit&quot; led panel (panel and power supply) for humid environments.



## Application domain

- Medical areas
- Washrooms
- Outdoor Circulations



## Electric data

Total power (W)	40
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	4000K
Light source type	-
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3800lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	595 x 595 x 26
Weight (kg)	1.82
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	-
IK Code	IK04
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-
Body material	Aluminium
Diffuser material	PC
Driver included	Yes

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none"><li>BL08000009 - INTEGRATION FRAME 600x600</li></ul>