

OFFICELINE 120-NR-30W-4000K-DALI-ENCASTRE-OPALE

BL06272006

INDOOR > Office Recessed Fixture

Recessed micro prismatic OFFICELINE 120 black 3CCT dimmable dali ideal for office lighting



Application domain

- School
- Office
- Circulations areas



Electric data

Total power (W)	27
Rated voltage (V)	230V
Distorsion harmonique	<10%
Power factor	>0.95
Network frequencies	60Hz
Electric class	I
Dimmable	Dali

Power supply data

Max. lamp per B10A circuit breaker	8
Max. lamp per B16A circuit breaker	12
Max. lamp per C16A circuit breaker	16

Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	-
SDCM	SDCM>3
IRC	>85
Safety group (EN62778)	RG0
Luminous flux (lm)	3300lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	1144 x 63 x 25
Weight (kg)	1.3
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	-
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-
Body material	-
Diffuser material	-
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	80°
Tiltable	No
Connection type	Fil à connecter