

FOG

# TF034-FOG-30W-IP66-WHITE-4000K-850°


BL12306501

**INDOOR** > Indoor Bulkhead

**OUTDOOR** > Outdoor Wall Light

**OUTDOOR** > Outdoor Bulkhead

Indoor or outdoor use, IP66, available with detector. Ideal for communities, garages and stairwells



## Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



28 W

2750  
lm

IRC  
>80

IP66

4000K

F



FILE UPDATED ON 30/01/2023

## Electric data

Total power (W)	28
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2750lm (4000K)
ULOR	-



FILE UPDATED ON 30/01/2023



## Technical data

Diameter (mm)	360
Height (mm)	93.5
Recessed diameter (mm)	-
Weight (kg)	1.28
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20... +50°
Body material	PC
Diffuser material	PC
Driver included	Yes
Recoverable	Non concerné

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	110°
Tiltable	No
Connection type	Connecteur rapide avec repiquage



FILE UPDATED ON 30/01/2023



## Atmosphere

---



PROTECTED BY

## Other

---



## Other

---



FILE UPDATED ON 30/01/2023