

NEODE

NEODE PROJ GU10

TR18355402

OUTDOOR > Outdoor Wall Light

OUTDOOR > Outdoor Flood Light

Outdoor floodlight delivered with stake. 316L stainless steel set.
Product for GU10 source (not included).



Application domain

- Outdoor residential
- Garden
- Outdoor lighting



Electric data

Total power (W)	-
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	-
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	-
Light source type	GU10
Including the light source	No
SDCM	-
IRC	-
Safety group (EN62778)	-
Luminous flux (lm)	-
ULOR	-

Technical data

Diameter (mm)	62
Height (mm)	135
Recessed diameter (mm)	-
Weight (kg)	0.8
Recessed depth under BA13 (mm)	-
Cable length	100 cm
Product color	Grey
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP66
Use temperature range	-20... +45°
Body material	STAINLESS STEEL 316L
Diffuser material	Verre trempé
Driver included	No

Supplementary data

Warranty period	5 years
Light beam spread	
Tiltable	Yes (180°)
Connection type	Fil à connecter