

TF099-FOG ASYM SENSOR-25W-IP66-WHITE-4000K-850°

BL12256503

INDOOR > Indoor Bulkhead**OUTDOOR** > Outdoor Wall Light**OUTDOOR** > Outdoor Bulkhead

Asymmetrical porthole with HF detector ideal for stairways, passageways and building surroundings.



Application domain

- Parkings lots and underground passages
- Circulations areas
- Stairs
- Outdoor Circulations



24 W

2500
lmUGR
<25IRC
>80

IP66

4000K



Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
UGR	<25
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2500lm (4000K)
ULOR	-

Technical data

Diameter (mm)	310
Height (mm)	115
Recessed diameter (mm)	-
Weight (kg)	1.22
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-20... +45°
Body material	PC
Diffuser material	PC
Sensor	Haute fréquence
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	110° X 90°
Tiltable	No
Connection type	Fast connect

