

CYLINDER

# CYLINDER 1200-DIAM 45-36W-IP65-4000K- TRANSPARENT

TR11366503

**INDOOR** > Surface mounted and suspended fixtures

**INDOOR** > Wall light

**INDOOR** > Triproof

**OUTDOOR** > Ceiling Lights

Waterproof tubular luminaire in polycarbonate and stainless steel.  
Suspended or projecting, it is both aesthetic and technical.



## Application domain

- Parkings lots and underground passages
- Production areas, assembly plant
- Circulations areas
- Stairs



## Electric data

|                       |         |
|-----------------------|---------|
| Total power (W)       | 28 / 36 |
| Rated voltage (V)     | 230V    |
| Distorsion harmonique | -       |
| Power factor          | >0.95   |
| Network frequencies   | 50Hz    |
| Electric class        | I       |
| Dimmable              | No      |

## Photometric data

|                            |                |
|----------------------------|----------------|
| Color temperatures         | 4000K          |
| Light source type          | SMD            |
| Including the light source | Yes            |
| SDCM                       | SDCM>4         |
| IRC                        | >80            |
| Safety group (EN62778)     | RG0            |
| Luminous flux (lm)         | 3640lm (4000K) |
| ULOR                       | -              |

## Technical data

|                                |                           |
|--------------------------------|---------------------------|
| Dimensions (mm)                | 1210 x 45 x 45            |
| Weight (kg)                    | 0.9                       |
| Recessed depth under BA13 (mm) | -                         |
| Cable length                   | 100 cm                    |
| Product color                  | -                         |
| IK Code                        | IK10                      |
| Incandescent wire test         | 650°C                     |
| IP Code                        | IP65                      |
| Use temperature range          | -25... +40°               |
| Body material                  | PC - STAINLESS STEEL 316L |
| Diffuser material              | PC                        |
| Driver included                | Yes                       |

## Liefe time

|           |          |
|-----------|----------|
| L70 à 25° | 50 000 h |
|-----------|----------|

## Supplementary data

|                   |                 |
|-------------------|-----------------|
| Warranty period   | 5 years         |
| Light beam spread | 120°            |
| Tiltable          | Yes (360°)      |
| Connection type   | Fil à connecter |

Other

---



Other

---



Other

---

