

LINE

## LINE 25W-3000K-36°-DIM-NR

BL02252002

**INDOOR** > Downlights (until 95 mm)

Recessed architectural led, gives depth to volumes. Low glare UGR<19, black with chrome reflector. Appreciated by decorators for its design, it does not dazzle and brings a real contemporary touch.



### Application domain

- Residential indoor
- Kitchen
- Home Office
- House Corridor
- Entrance Halls
- Shop



25 W

1500  
lmUGR  
<19IRC  
>90

IP40

3000K



## Electric data

Total power (W)	25
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

## Photometric data

Color temperatures	3000K
UGR	<19
Light source type	-
SDCM	SDCM>4
IRC	>90
Safety group (EN62778)	RG1
Luminous flux (lm)	1500lm (3000K)
ULOR	-

## Technical data

Dimensions (mm)	45 x 280 x 51
Recessed diameter (mm)	Min. : 37   Max. : 272
Weight (kg)	0.54
Recessed depth under BA13 (mm)	60
Cable length	-
Product color	Black
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP40
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	-
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	36°
Tiltable	No
Connection type	Connector on the product

