

LED PORTHOLE

FOG 360-4000K-IP66

BL12256506

INDOOR > Indoor Bulkhead

OUTDOOR > Outdoor Bulkhead

Led porthole with external quick connector, IK10 and IP66



Application domain

- Parkings lots and underground passages
- School
- Cloakrooms
- Outdoor Circulations



24 W

2400
lm

IRC
>80

IP66

4000K

F



FILE UPDATED ON 28/02/2023

Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	-
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2400lm (4000K)
ULOR	-



FILE UPDATED ON 28/02/2023

Technical data

Diameter (mm)	310
Height (mm)	115
Recessed diameter (mm)	-
Weight (kg)	1.06
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP66
Use temperature range	-25... +45°
Body material	PC
Diffuser material	PC
Driver included	Yes

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	fast connector



FILE UPDATED ON 28/02/2023

