

FLOOR RECESSED AND LED BEACON

ANDROMEDE ENC 316L RGB 12V

TR16056704

OUTDOOR > Groundlight

Recessed floor and RGB led beaconing. Highlight your exteriors!



Application domain

- Outdoor residential
- Garden
- Outdoor illumination
- Outdoor Circulations
- Outdoor lighting



0.5 W

10 lm

IRC
>80

IP65

RGB

Electric data

Total power (W)	0.5
Rated voltage (V)	12Vdc
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III
Dimmable	No

Photometric data

Color temperatures	RGB
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	10lm (RGB)
ULOR	-

Technical data

Diameter (mm)	35
Height (mm)	27.5
Recessed diameter (mm)	30
Weight (kg)	0.12
Recessed depth under BA13 (mm)	-
Cable length	50 cm
Product color	Grey
IK Code	IK08
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-20... +45°
Body material	-
Diffuser material	PC
Driver included	No

Liefe time

L70 à 25°

25 000 h

Supplementary data

Warranty period	3 years
Light beam spread	90°
Tiltable	No
Connection type	fast connector
Linked products	<ul style="list-style-type: none">• TR16000003 - ANDROMEDE RGB CONTROLLER• TR16000002 - ANDROMEDE RGB PRODUCT EXTENDER• TR16000004 - ANDROMEDE EXTENSION & RGB PSU

Other

Other

INSTALLATION : Jusqu'à 8 produits en ligne

