

LED DOWNLIGHT

STORM THOR ROTATIF 15W-36°-3000K- ROND-WHITE- DIMM

TR01152001

INDOOR > Downlight (100 to 240 mm)

Snail type 360° adjustable accent led
downlight.



Application domain

- Entrance Halls
- Shop



15 W

1200
lmIRC
>85

IP20

3000K

E

Electric data

Total power (W)	15
Rated voltage (V)	230V
Distorsion harmonique	<12%
Power factor	>0.95
Network frequencies	50Hz
Electric class	II
Dimmable	Triac

Power supply data

Max. lamp per B10A circuit breaker	30
Max. lamp per B16A circuit breaker	35
Max. lamp per C16A circuit breaker	40

Photometric data

Color temperatures	3000K
Light source type	COB
Including the light source	Yes
SDCM	-
IRC	>85
Safety group (EN62778)	RG1
Luminous flux (lm)	1200lm (3000K)
ULOR	-

Technical data

Diameter (mm)	145
Height (mm)	102
Recessed diameter (mm)	Min. : 120 Max. : 130
Weight (kg)	0.56
Recessed depth under BA13 (mm)	110
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	-
Driver included	Yes
Recoverable	Non recouvrable

Liefe time

L80 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	36°
Tiltable	Yes (45°)