

# PANEL PURE CLEAN 40W-UGR19-600X600- IP65-ANTIBACTERIEN

TR04402007

**INDOOR** > Office Recessed Fixture

LED panel in aluminum and antibacterial polycarbonate. Clean room type device designed for operating theaters but also examination rooms, waiting areas, retirement homes, nurseries...



## Application domain

- School
- Medical areas
- Cloakrooms
- Washrooms



## Electric data

|                       |             |
|-----------------------|-------------|
| Total power (W)       | 40          |
| Rated voltage (V)     | 230V        |
| Distorsion harmonique | -           |
| Power factor          | >0.9        |
| Network frequencies   | 50Hz , 60Hz |
| Electric class        | II          |
| Dimmable              | No          |

## Photometric data

|                            |                |
|----------------------------|----------------|
| Color temperatures         | 4000K          |
| UGR                        | <19*           |
| Light source type          | SMD            |
| Including the light source | Yes            |
| SDCM                       | SDCM>4         |
| IRC                        | >80            |
| Safety group (EN62778)     | RG0            |
| Luminous flux (lm)         | 3800lm (4000K) |
| ULOR                       | -              |

## Technical data

|                                |               |
|--------------------------------|---------------|
| Dimensions (mm)                | 595 x 595 x 9 |
| Weight (kg)                    | 2.46          |
| Recessed depth under BA13 (mm) | -             |
| Cable length                   | -             |
| Product color                  | White         |
| IK Code                        | IK07          |
| Incandescent wire test         | 650°C         |
| IP Code                        | IP65 facade   |
| Use temperature range          | -20... +45°   |
| Body material                  | Aluminium     |
| Diffuser material              | PC - PS       |
| Driver included                | Yes           |

## Liefe time

|           |          |
|-----------|----------|
| L80 à 25° | 50 000 h |
|-----------|----------|

## Supplementary data

|                   |  |
|-------------------|--|
| Warranty period   | 5 years  |
| Light beam spread | 110°   |
| Tiltable          | No   |
| Connection type   | Connecteur rapide avec repiquage   |
| Linked products   | <ul style="list-style-type: none"><li>• BL08000009 - INTEGRATION FRAME 600x600</li></ul> |