

## OUTDOOR WALL

**BIM APP 10W-3000K-U&D-IP65-WHITE**

BL05102001

**OUTDOOR** > Outdoor Wall Light

Indoor or outdoor wall light, up and down lighting (2x5W). Angle of light diffusion adjustable thanks to shutters. Ideal to create an atmosphere that is both modern and friendly.

**Application domain**

- Outdoor residential
- Garden
- Outdoor illumination
- Bedroom
- House Corridor
- Entrance Halls
- Outdoor lighting



10 W

900 lm

IRC  
>80

IP65

3000K

D



FILE UPDATED ON 27/01/2023

## Electric data

Total power (W)	10
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz , 60Hz
Electric class	I
Dimmable	No

## Photometric data

Color temperatures	3000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG1
Luminous flux (lm)	900lm (3000K)
ULOR	-



FILE UPDATED ON 27/01/2023



## Technical data

Dimensions (mm)	96 x 120 x 100
Weight (kg)	0.58
Recessed depth under BA13 (mm)	-
Cable length	0
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	20° X 90°
Tiltable	No
Connection type	Connector on the product
Linked products	<ul style="list-style-type: none"><li>BL05102002 - BIM APP 10W-3K-U&amp;D-IP65-G</li></ul>



FILE UPDATED ON 27/01/2023

