

LED PANEL

TF043-PANEL IP65 Facade 600x600 36w 4000K

BL04362001

INDOOR > Office Recessed Fixture

Led panel IP65 facade, ideal for kitchens, technical rooms, certain laboratories...



Application domain

- School
- Medical areas
- Washrooms



Electric data

Total power (W)	36
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	3600lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	595 x 595 x 10
Recessed diameter (mm)	Min. : 600 Max. : 600
Weight (kg)	2.74
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK07
Incandescent wire test	650°C
IP Code	IP65 facade
Use temperature range	-20... +40°
Body material	Aluminium
Diffuser material	PC - PS
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	3 years
Light beam spread	110°
Tiltable	No
Linked products	<ul style="list-style-type: none">• BL08000009 - INTEGRATION FRAME 600x600