

FLOOR RECESSED AND LED BEACON

# BOREALE ENC 316- 4W 3000K

TR16046501

**OUTDOOR** > Groundlight

Floor recessed in 316L stainless steel. Resists strong climatic disturbances (saline air, treated water). Low voltage for installation at the edge of a body of water.



## Application domain

- Outdoor residential
- Garden
- Outdoor illumination
- Outdoor Circulations
- Outdoor lighting



## Electric data

Total power (W)	4
Rated voltage (V)	24Vdc
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	III
Dimmable	No

## Photometric data

Color temperatures	3000K
UGR	<19
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	460lm (3000K)
ULOR	-

## Technical data

Diameter (mm)	76
Height (mm)	54
Recessed diameter (mm)	-
Weight (kg)	0.5
Recessed depth under BA13 (mm)	-
Cable length	90 cm
Product color	Grey
IK Code	IK10
Incandescent wire test	850°C
IP Code	IP68
Use temperature range	-25... +45°
Body material	STAINLESS STEEL 316L
Diffuser material	Verre trempé
Driver included	No
Recoverable	Non concerné

## Liefe time

L70 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	45°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none"><li>TR09406524 - Meanwell BOREALE Power Supply</li></ul>

