

CEILING LIGHT

HALO 15W-IP40-3CCT-WHITE

BL12155411

INDOOR > Indoor Bulkhead

INDOOR > Surface mounted and suspended fixtures

INDOOR > Wall light

Contemporary porthole, installs as well in ceiling as in wall.



Application domain

- Residential indoor
- Kitchen
- Bathroom
- Bedroom
- Home Office
- House Corridor
- Home Cellar, House Technical Room
- Circulations areas
- Stairs
- Entrance Halls



14 W

1600
lm

IRC
>80

IP40

3 CCT

3000K / 4000K
5700K

C

Electric data

Total power (W)	14
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

Photometric data

Color temperatures	3000K / 4000K / 5700K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	1600lm (4000K)
ULOR	-

Technical data

Diameter (mm)	300
Height (mm)	52
Recessed diameter (mm)	-
Weight (kg)	1
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP40
Use temperature range	-25... +45°
Body material	PC
Diffuser material	PC
Driver included	No

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	130°
Tiltable	No
Connection type	Bornier avec repiquage

Atmosphere



Atmosphere

