

LED PANEL

# PANEL PURE CONFORT12-24W-UGR12- 4000K-BLACK

TR04302009

**INDOOR** > Office Recessed Fixture

With a very high visual comfort, the Comfort UGR12 is ideal for classes, activities that require intense visual work or that require an environment without light aggressiveness.



## Application domain

- Meeting room
- School
- Office



24 W

3000  
lmUGR  
<12IRC  
>84

IP20

4000K



## Electric data

Total power (W)	24
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz , 60Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	4000K
UGR	<12
Light source type	COB
Including the light source	Yes
SDCM	SDCM>4
IRC	>84
Safety group (EN62778)	RG1
Luminous flux (lm)	3000lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	595 x 595 x 34
Weight (kg)	3.8
Recessed depth under BA13 (mm)	-
Cable length	-
Product color	Black
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP20
Use temperature range	-20... +45°
Body material	Iron
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	5 years
Light beam spread	70°
Tiltable	No
Connection type	Connecteur rapide avec repiquage

## Atmosphere

---



## Other

---



## Other

---

