

LED TUBULAR

CYLINDER 1500 DIAM70-50W-IP65-4000K- TRANSPARENT

TR11506502

INDOOR > Surface mounted and suspended fixtures

INDOOR > Wall light

INDOOR > Triproof

OUTDOOR > Ceiling Lights

Waterproof tubular LED pendant luminaire in polycarbonate and stainless steel. Suspended or projecting, it is both aesthetic and technical.



Application domain

- Parkings lots and underground passages
- Production areas, assembly plant
- Circulations areas
- Stairs



Electric data

Total power (W)	50
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.95
Network frequencies	50Hz
Electric class	I
Dimmable	No

Photometric data

Color temperatures	4000K
Light source type	SMD
Including the light source	Yes
SDCM	SDCM>5
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	4700lm (4000K)
ULOR	-

Technical data

Dimensions (mm)	1510 x 75 x 75
Weight (kg)	1.9
Recessed depth under BA13 (mm)	-
Cable length	100 cm
Product color	-
IK Code	IK10
Incandescent wire test	650°C
IP Code	IP65
Use temperature range	-25... +40°
Body material	STAINLESS STEEL 316L
Diffuser material	PC
Driver included	Yes

Liefe time

L70 à 25°	50 000 h
-----------	----------

Supplementary data

Warranty period	5 years
Light beam spread	120°
Tiltable	No
Connection type	Fil à connecter
Linked products	<ul style="list-style-type: none">• TR11000001 - CYLINDER SUSPENSION KIT• TR11000002 - CYLINDER CABLE 3M TRANSL• TR11000005 - CYLINDER BOX CONNECTION

Other



Other



Other

