

## DOWNLIGHT

# DOWNLIGHT-SQUARE-20W-PRISM-3CCT- 3000K-4000K-5700K

BL02202002

**INDOOR** > Downlight (100 to 240 mm)

Square downlight with prismatic diffuser. Very low glare with a slight setback for the diffuser. Separate power supply with 3 temperature colors possible to change on the product!



### Application domain

- Meeting room
- Home Office
- Circulations areas
- Cloakrooms
- Entrance Halls



20 W

2000  
lm

UGR  
<19

IRC  
>80

IP40

3 CCT

3000K / 4000K  
5700K



## Electric data

Total power (W)	20
Rated voltage (V)	230V
Distorsion harmonique	-
Power factor	>0.9
Network frequencies	50Hz
Electric class	II
Dimmable	No

## Photometric data

Color temperatures	3000K / 4000K / 5700K
UGR	<19
Light source type	-
Including the light source	Yes
SDCM	SDCM>4
IRC	>80
Safety group (EN62778)	RG0
Luminous flux (lm)	2000lm (4000K)
ULOR	-

## Technical data

Dimensions (mm)	180 x 180 x 68
Weight (kg)	0.72
Recessed depth under BA13 (mm)	68
Cable length	-
Product color	White
IK Code	IK06
Incandescent wire test	650°C
IP Code	IP40
Use temperature range	-20... +45°
Body material	Aluminium
Diffuser material	PC
Driver included	Yes
Recoverable	Non recouvrable

## Liefe time

L80 à 25°	50 000 h
-----------	----------

## Supplementary data

Warranty period	3 years
Light beam spread	90°
Tiltable	No
Connection type	Fil à connecter

